

DO NOT SCALE

UNLESS NOTED DIMENSIONS

ARE IN INCHES

TOLERANCES

± 0.02 IN/IN

WEIGHT

[CENTIMETERS]

[± 0.05 CM/CM]

44 Ib SIZE DRAWING NUMBER

CROBICS

SHEET

1 OF 1

BETTER WATER, BETTER WORLD.

REV. INI-01-D

20 GPM Grease Interceptor

FOGHOG FH-20

MATERIALS OF CONSTRUCTION

- 1. The holding tank shall be constructed of cross-linked polyethylene for structural integrity, durability and high heat temperature resistance with a smooth interior finish for ease of cleaning.
- 2. Interceptor baffles shall be constructed of temperature resistant Acrylonitrile Butadiene Styrene (ABS) for its high heat and impact resistant properties.
- 3. The integrated heat resistant neoprene gaskets will be used to seal all plumbing connections
- 4. The interceptor cover will be constructed of rigid ABS and shall be installed with corrosion resistant stainless steel fasteners.
- 5. The liquid level in the grease interceptor shall be maintained by our proprietary device which regulates head conditions to assure proper retention levels. The inlet and outlet assemblies shall be constructed of PVC Schedule 40 Pipe and associated fittings. The inlet and outlet fittings my be substituted with metal fittings, depending on local plumbing codes.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BIO-MICROBICS INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BIO-MICROBICS INC. IS PROHIBITED, DESIGN AND INVENTION RIGHTS ARE RESERVED. IN THE	BIO-MICROBICS © 2014	DRAWN CTC	DATE 8/14/2006	Α	FOGH
INTEREST OF TECHNOLOGICAL ADVANCEMENT, ALL PRODUCTS ARE SUBJECT TO DESIGN AND OR MATERIAL CHANGE WITHOUT NOTICE.		CHECKED PF	10/21/2013	í – – –	REVISED 10/21/2013